

# Dimmable 12W LED Downlight

Model: LDL125-WH



## DIMENSIONS

Flange 148mmØ x138mm height  
Fits holes 125mm to 135mmØ  
Hole cut: 125  
Cavity depth: 180  
Side clearance: 25

## TECHNICAL DATA

Total lumens: 900  
Colour temp: 3,000K  
Power supply: 220-240V, Double Insulated  
Dimmable: Yes  
CRI: 81  
Wattage: 12  
Beam angle: 60°  
Control gear: Included

## FEATURES

- Optimised Non Glare Downlights
- LED's set back and anti glare baffle for low glare U.G.R.
- Aluminium body - forward traveling heat sinking to dissipate heat below the ceiling to ensure optimum life
- Samsung brand LED technology
- Integral driver for easy installation
- Quick and economical installation, only one connection - large looping mains terminals
- Beam angle 60 degrees and with extra spill light for good general room lighting.
- Equivalent to 100Watt Incandescent
- Dimmable down to 30% of full brightness
- 180lux at 1.5metres
- 65lux at 2.4metres

## SPECIFICATIONS

IC  
Material: Aluminium  
Lamp included: Yes  
Number of lamps: 1  
Air / Moisture Transfer: Closed  
IP Rating: IP44  
Technology field: LED  
Indoor / Outdoor: Indoor  
Mounting type: Ceiling, Recessed  
Colour: White

