



DIMENSIONS

Flange 105mmØ
Hole cut: 90
Cavity depth: 210
Side clearance: 50

TECHNICAL DATA

Total lumens: 480
Colour temp: 3,000K
Power supply: 220-240V, Double Insulated
CRI: 82
Wattage: 6
Beam angle: 38°
Control gear: Included

FEATURES

- Fire rated to 60/60/60 minutes
- Engineered for fire safety and energy efficiency- sets the industry standard for downlight safety
- Thermal cut-off and auto reset function for protection against misuse and overloading.
- 6watt LED bulb comparable to 50watt halogen downlight
- Reflector bulb designed to give uniform light spread with no hot spots or demarcation lines in light beam
- 480 lumens, CRI (RA) 82
- Beam angle 38° degree
- Integral driver for easy installation
- Aluminium die cast face
- Both lamp and downlight have heat sink technology for effective thermal management
- Tiltable to 40° and fully rotatable
- Downlight Classification = CA135
- 5 year transformer warranty

SPECIFICATIONS

CA135
Lamp included: Yes
Lamp holder type: MR16
Number of lamps: 1
Air / Moisture Transfer: Closed
Technology field: Halogen, LED Replaceable
Indoor / Outdoor: Indoor
Mounting type: Ceiling, Recessed
Colour: White