


| DIMENSIONS   | TECHNICAL DATA  | FEATURES  | SPECIFICATIONS   |
|--|---|---|--|
| <ul style="list-style-type: none"> <li>• 900mmH</li> <li>• 275mmØ</li> </ul> | <p>Total lumens: 265</p> <p>Colour temp: 2,800K</p> <p>Power supply: Solar</p> <p>CRI: 80</p> <p>Wattage: 1.5W</p> <p>Beam angle: 77°</p> | <ul style="list-style-type: none"> <li>• Part of our Freelite™ solar lighting range</li> <li>• Night Sky Friendly ULOR =0.77%</li> <li>• Offers you control over ighting preferences boasting 6 different lighting mode options</li> <li>• Built in microwave sensor, range: 8 Metres, 360°</li> <li>• Smart Energy Management system provides lighting over 2-3 days of cloud</li> <li>• Made with quality Aluminium and UV stabilised polycarbonate</li> <li>• IK10 vandal resistant material and theft proof design with concealed fixings ideal for public areas</li> <li>• Solar lighting offers a much cheaper, hassle-free installation compared with traditional lighting. With no trenching, cables, or conduits required, these costs are eliminated</li> <li>• 5 year warranty with expected battery life of 8 to 14 years when well situated - view warranty info here.</li> <li>• Battery replaceable</li> <li>• Find out more about our Freelite™ Solar range here in our Solar Lighting Hub</li> <li>• Read more about Night Sky Friendly lighting here in our blog article</li> </ul> | <p>Material:<br/>                 Die-Cast Aluminium, UV Stabilised Polycarbonate</p> <p>Lamp included: Yes</p> <p>IP Rating: IP65</p> <p>Technology field: LED</p> <p>Indoor / Outdoor: Outdoor</p> <p>Mounting type: Post Lights</p> |

**Lighting Distribution Pattern:**

Horizontal axis shows 180° beam angle.



**Lighting Distribution Pattern:**

Vertical axis 77° beam angle.

