




Lighting Distribution Pattern:

Horizontal axis shows 360° beam angle.



DIMENSIONS	TECHNICAL DATA	FEATURES	SPECIFICATIONS
• 900mmH • 275mmØ	Total lumens: 270 Colour temp: 2,800K Power supply: Solar CRI: 80 Wattage: 1.5W Beam angle: 130°	• Part of our Freelite™ solar lighting range • Night Sky Friendly ULOR =1.04% • Offers you control over ighting preferences boasting 6 different lighting mode options • Built in microwave sensor, range: 8 Metres, 360° • Smart Energy Management system provides lighting over 2-3 days of cloud • Made with quality Aluminium and UV stabilised polycarbonate • IK10 vandal resistant material and theft proof design with concealed fixings ideal for civic public areas • Solar lighting offers a much cheaper, hassle-free installation compared with traditional lighting. With no trenching, cables, or conduits required, these costs are eliminated • 5 year warranty with expected battery life of 8 to 14 years when well situated - view warranty info here. • Battery replaceable • Find out more about our Freelite™ Solar range here in our Solar Lighting Hub • Read more about Night Sky Friendly lighting here in our blog article	Material: Die-Cast Aluminium, UV Stabilised Polycarbonate Lamp included: Yes IP Rating: IP65 Technology field: LED Indoor / Outdoor: Outdoor Mounting type: Post Lights

